

## Modular Cooking Range Line 900XP Electric Chip Scuttle

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



391098 (E9CSPDC000)

Electric Chip Scuttle Top with

## **Short Form Specification**

#### Item No.

Heating via infrared heating elements positioned on the back of the unit. Perforated false bottom GN 1/1 specially shaped for easier food collection. One piece pressed worktop in stainless steel. Easy to use control panel with ON/OFF switch. Exterior panels in stainless steel. Design of control knobs protects against water infiltration.

#### **Main Features**

- Typically used in combination with a fryer to allow fried portions to drip excess oil into the well basin.
- The appliance is used to keep servings warm until ready to be served to customer.
- Unit to have infrared heating elements positioned on the back of the unit to increase holding time.
- Well able to contain 1/1 GN container with a maximum height of 150 mm.
- Easy-to-use control panel.
- Unit supplied with a perforated GN 1/1 false bottom specially shaped for easier food collection.
- One-piece pressed working top in 2mm stainless steel with Scotch Brite finish to facilitate cleaning.
- All major compartments located in front of unit for ease of maintenance.
- The special design of the control knob system guarantees against water infiltration.
- Suitable for countertop installation.

### Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPX5 water resistance certification.

#### APPROVAL:





## Modular Cooking Range Line 900XP Electric Chip Scuttle

## **Optional Accessories**

<ul> <li>Junction sealing kit</li> </ul>	PNC 206086	
<ul> <li>Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels</li> </ul>	PNC 206135	
<ul> <li>Support for bridge type installation, 800mm</li> </ul>	PNC 206137	
<ul> <li>Support for bridge type installation, 1000mm</li> </ul>	PNC 206138	
<ul> <li>Support for bridge type installation, 1200mm</li> </ul>	PNC 206139	
<ul> <li>Support for bridge type installation, 1400mm</li> </ul>	PNC 206140	
<ul> <li>Support for bridge type installation, 1600mm</li> </ul>	PNC 206141	
<ul> <li>Support for bridge type installation, 400mm</li> </ul>	PNC 206154	
<ul> <li>Chimney upstand, 400mm</li> </ul>	PNC 206303	
Back handrail 800 mm	PNC 206308	
Back handrail 1200 mm	PNC 206309	
<ul> <li>Side handrail-right/left hand (900XP)</li> </ul>	PNC 216044	
<ul> <li>Frontal handrail, 400mm</li> </ul>	PNC 216046	
<ul> <li>Frontal handrail, 800mm</li> </ul>	PNC 216047	
<ul> <li>Frontal handrail, 1200mm</li> </ul>	PNC 216049	
<ul> <li>Frontal handrail, 1600mm</li> </ul>	PNC 216050	
<ul> <li>Large handrail - portioning shelf, 400mm</li> </ul>	PNC 216185	
<ul> <li>Large handrail - portioning shelf, 800mm</li> </ul>	PNC 216186	





# Modular Cooking Range Line 900XP Electric Chip Scuttle

## Front 5 7/8 " 150 mm Side 19 1/4 " E 490 I 2 3/16 " 56 mm

Electrical inlet (power)


3 1/4 "

82 mm

610 mm

27 7/8 "

708 mm



ΕQ

### **Electric**

11 3/8 " 290 mm 251 mm

Top

15/16 24 mm Supply voltage:

391098 (E9CSPDC000) 220-230 V/1 ph/50/60 Hz

Electrical power max.: 1 kW **Total Watts:** 1 kW

220-230V 1~ 50/60Hz

0,9-1kW Predisposed for:

## **Key Information:**

Usable well dimensions

(width): 306 mm

Usable well dimensions

(height):

156 mm

Usable well dimensions (depth):

510 mm

External dimensions, Width: External dimensions, Depth:

400 mm 930 mm

External dimensions, Height:

250 mm 28 kg

Net weight: Shipping weight: Shipping height:

ISO 9001 kg 640 mm

Shipping width: Shipping depth: Shipping volume:

480 mm 1020 mm 0.31 m<sup>3</sup>

Certification group:

ECS9

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



Modular Cooking Range Line 900XP Electric Chip Scuttle