

Infrared thermometer

271148

Laser pointer for accurate targeting. Measuring range: -32 to +400°C. Gradation: 0.1°C, accuracy: up to $\pm 1.5^\circ\text{C}/\pm 1.5\%$. The ratio of the measuring distance to the area to be measured: 12:1. "Lock mode" function for continuous temperature monitoring. Automatic switch off. Power supply: 9 V battery, included in the set.



Specifications

Temp range from [°C]	: -32°C
Temp range to [°C]	: 400°C
Unit temperature	: Fahrenheit, Celsius
Battery included	: Yes

Packed per	: 1
Packaging type	: Box
Length (mm)	: 37
Width (mm)	: 70
Height (mm)	: 150
Control panel	: Digital
Measurements	: 37x70x(H)150

Transport specifications

EAN	: 8711369271148
Intrastat code	: 90251900
Gross weight (kg)	: 0.22
Net weight (kg)	: 0.164

(Inner) packaging length (mm)	: 390
(Inner) packaging width (mm)	: 169
(Inner) packaging height (mm)	: 220
Quantity per (inner) package	: 10
Export carton length (mm)	: 518
Export carton width (mm)	: 414
Export carton height (mm)	: 464
Quantity per export carton	: 60
Sales units per pallet	: 480
Plastic packaging (gram)	: 38

HENDI B.V.
Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu