

Fast response thermometer

271230

Provides fast and accurate temperature readings. IP65 waterproof. Measuring range -50°C to 350°C, unit of measurement °C or °F. Gradation 0,1°C, accuracy $\approx 0,8\%/0,8^{\circ}\text{C}$. Hold function - saves momentary temperature. 130 mm stainless steel probe. Turns off automatically. With probe cover. Battery included.



Specifications

Temp range from (°C)	: -50°C
Temp range to (°C)	: 350°C
Unit temperature	: Fahrenheit, Celsius
Battery included	: Yes
Materials	: PC (Polycarbonate), Stainless steel

Packed per	: 1
Packaging type	: Box
Length (mm)	: 204
Width (mm)	: 42
Height (mm)	: 20
Control panel	: Digital
Measurements	: 204x42x(H)20

Transport specifications

EAN	: 8711369271230
Intrastat code	: 90251900
Gross weight (kg)	: 0.13
Net weight (kg)	: 0.081

(Inner) packaging length (mm)	: 504
(Inner) packaging width (mm)	: 269
(Inner) packaging height (mm)	: 160
Quantity per (inner) package	: 20
Export carton length (mm)	: 570
Export carton width (mm)	: 529
Export carton height (mm)	: 330
Quantity per export carton	: 80
Sales units per pallet	: 960
Plastic packaging (gram)	: 32

HENDI B.V.
Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu