

Griddle

154922

Housing made of stainless steel. The solid 8 mm thick hardened steel plate offers excellent heat retention. Fitted with backsplashes and a removable drip tray. Temperature stepless adjustable up to 300°C. Overheating protection by means of a resettable thermal cutout. Power switch with integrated indication lamp. Fitted with non-slip feet.

Griddle measures 316x380 mm and is entirely smooth.



Specifications

Voltage	: 220-240
Temp range to (°C)	: 300°C
Unit temperature	: Celsius
Cord length (mm)	: 1500
Protections	: Overheat protection
Electrician needed	: No
Materials	: Stainless steel

Packed per	: 1
Packaging type	: Box
Length (mm)	: 326
Width (mm)	: 445
Height (mm)	: 225
Weight of item (kg)	: 13.5
Power (input) (W)	: 2000
Control panel	: Analog
Programmable	: No
Measurements	: 326x445x(H)225

Transport specifications

EAN	: 8711369154922
Intrastat code	: 84198180
Gross weight (kg)	: 14.75
Net weight (kg)	: 13.21
Sales units per pallet	: 24
Plastic packaging (gram)	: 227

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu