

Double induction cooker Kitchen Line

239414

Very clean design suitable for live cooking. Very flat housing with black coated stainless steel frame. Surface of ceramic glass with integrated digital display.

Touch-sensitive controls, power or temperature adjustable in 9 steps. With boost mode which temporarily shifts some power from right hob to the left hob, providing up to 2000W. The left side hob can output 1800W, or 2000W while the boost function is active. The right side hob can output 1700W. Temperature range: 35-240°C. Suitable for pans with bottom diameter between 120 and 220 mm. With timer function for 0-180 minutes. Equipped with electronic protection against overheating. Maximum load of the induction cooker: 2x15 kg.



Specifications

Voltage	: 230
Electrician needed	: No
Materials	: Stainless steel
Packed per	: 1
Packaging type	: Box
Length (mm)	: 608
Width (mm)	: 405
Height (mm)	: 54
Power (input) (W)	: 3500
Programmable	: No
Measurements	: 608x405x(H)54

Transport specifications

EAN	: 8711369239414
Intrastat code	: 84198180
Gross weight (kg)	: 7.49
Net weight (kg)	: 6.51
Export carton length (mm)	: 675
Export carton width (mm)	: 225
Export carton height (mm)	: 472
Quantity per export carton	: 2
Sales units per pallet	: 36
Plastic packaging (gram)	: 172

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu