

Induction cooker 2000W Kitchen Line

239391

Very clean design suitable for live cooking. Very flat housing with black coated stainless steel frame. Surface of ceramic glass with integrated digital display.

Touch-sensitive controls, power or temperature adjustable in 11 steps. Temperature range: 35-240°C. Suitable for pans with bottom diameter between 120 and 220 mm. With timer function for 0-180 minutes. Equipped with electronic protection against overheating. Maximum load of the induction cooker: 15 kg.



Specifications

Voltage	: 230
Electrician needed	: No
Materials	: Stainless steel
Packed per	: 1
Packaging type	: Box
Length (mm)	: 297
Width (mm)	: 411
Height (mm)	: 57
Power (input) (W)	: 2000
Programmable	: No
Measurements	: 297x411x(H)57

Transport specifications

EAN	: 8711369239391
Intrastat code	: 84198180
Gross weight (kg)	: 4.18
Net weight (kg)	: 3.61
Export carton length (mm)	: 518
Export carton width (mm)	: 374
Export carton height (mm)	: 489
Quantity per export carton	: 6
Sales units per pallet	: 72
Plastic packaging (gram)	: 90

HENDI B.V.
 Innovatielaan 6
 6745 XW De Klomp, The Netherlands
 T: +31 (0)317 681 040
 E: info@hendi.eu

HENDI Polska Sp. z o.o.
 ul. Firmowa 12
 62-023 Robakowo, Poland
 T: +48 61 6587000
 E: info@hendi.pl

HENDI GmbH
 Ehrling 15
 5112 Lamprechtshausen, Austria
 T: +43 (0) 6274 200 10 0
 E: office.austria@hendi.eu

HENDI S.R.L.
 Str. 13 decembrie 94A, Hala 14
 Braşov, 500164, Romania
 T: +40 268 320330
 E: office@hendi.ro

PKS HENDI South East Europe SA
 5 Metsovou Str.
 18346 Moschato, Athens, Greece
 T: +30 210 4839700
 E: info@pks-hendi.com

HENDI Italia S.R.L.
 Via Leonardo da Vinci 4
 39100 Bolzano (BZ), Italy
 T: 800 727 438
 E: office.italy@hendi.eu