





TC85

Ice Maker

Product Features


- Cubed ice approx. 31x35x31mm (18 g)
- Production Capacity: 85 kg/24 h
- Storage Capacity: 40 kg
- Low energy air-cooled system
- Spray system produces individual clear ice cubes
- Self-contained ice machine with storage
- Ag+ easy to clean surfaces in the storage bin
- High quality SS304 stainless steel
- 4 Legs and 4 adjustable feet included
- Scoop for ice cubes included
- Built-in silent operating magnetic water pump
- Waste water drain pump for safe water drainage

Clear ice maker machine in stainless steel

The TC range of ice makers uses a spray system to produce crystal clear, slow melting ice cubes. This makes the unit ideal for use in cafes, restaurants, pubs, bars, fast-food venues, and other hospitality establishments that require ice for drinks, cocktails, or keeping food such as fresh fish cool. The exterior of the unit is made from 304 stainless steel; the door at the front of the unit allows quick access to an insulated storage bin, which features Ag+ antibacterial technology to help prevent the formation of bacteria and odors. To ensure that the ice cube maker runs efficiently, the unit has a air filter that is easy to remove and clean. The TC ice maker uses a low energy air-cooled system, which means it takes in the surrounding air and uses this to cool down the refrigeration system. The capacity of the ice maker is therefore affected by the ambient temperature surrounding it as well as the temperature of the water it takes in.

Easy to clean

condenser filter



Ice cube dimensions

Capacity Ice Production	kg/24h	85
Capacity In Ice Container	kg	40
Size of Ice Cubes	mm	31 x 35 x 31 (18g)
Water Consumption	l/24h	129
Climate Class		5
Gross / Net Weight	kg	94 / 85
Design and Material		
Feet / Legs		4 adjustable feet and legs
Exterior Finish		SS304
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Static
Refrigerant		R290
Refrigerant Charge	g	125
Power and Consumption		
Energy Consumption	kWh/24h	16.4
Annual Energy Cons.	kWh/year	5986
Power		1
Max Ambient		40°C at 40% RH
Input Power	W	1000
Voltage / Frequency	V/Hz	220-240/50
Dimensions		
External Dimension (WxDxH)	mm	738 x 600 x 822
Packed Dimension (WxDxH)	mm	800 x 660 x 1000
40ft Container Load	pcs	102

Measures and Content