

# Thermo-insulated container with heating function – catering

707692

Double HDPE impact-resistant insulating walls. It keeps food at safe serving temperatures for up to 4 hours after unplugging. 2 large ergonomic handles. Large and easy-to-read LED display indicating the temperature in the chamber. Maintains both high and low content temperature. Punched rails in the chamber housing. Suitable for 1/1 GN containers: – GN 1/1 (H) 20 mm: 12 pcs. – GN 1/1 (H) 65 mm: 6 pcs. – GN 1/1 (H) 100 mm: 4 pcs. – GN 1/1 (H) 150 mm: 3 pcs. – GN 1/1 (H) 200 mm: 2 pcs. – GN 1/2 (H) 150 mm: 6 pcs. Max. temperature: 68°C. Water resistance class: IPX3.



## Specifications

Temp resistance to [°C]	: 68°C
Voltage	: 220-240
Rated Frequency (Hz)	: 50 Hz, 60 Hz
Nestable	: No
Collapsible	: No
Materials	: HDPE (High density Polyethylene)
Marketing Packed per	: 1
Length (mm)	: 477
Width (mm)	: 680
Height (mm)	: 620
Internal length (mm)	: 335
Internal width (mm)	: 533
Internal height (mm)	: 590
GN size	: GN 1/1
Capacity unit	: Trays
Power (input) (W)	: 200
Measurements	: 477x680x(H)620

## Transport specifications

EAN	: 8711369707692
Intrastat code	: 85167970
Gross weight (kg)	: 22.61
Net weight (kg)	: 20.78
Sales units per pallet	: 5
Plastic packaging (gram)	: 1

### HENDI B.V.

Innovatielaan 6  
6745 XW De Klomp, The Netherlands  
T: +31 (0)317 681 040  
E: info@hendi.eu

### HENDI Polska Sp. z o.o.

ul. Firmowa 12  
62-023 Robakowo, Poland  
T: +48 61 6587000  
E: info@hendi.pl

### HENDI GmbH

Ehring 15  
5112 Lamprechtshausen, Austria  
T: +43 (0) 6274 200 10 0  
E: office.austria@hendi.eu

### HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14  
Braşov, 500164, Romania  
T: +40 268 320330  
E: office@hendi.ro

### PKS HENDI South East Europe SA

5 Metsovou Str.  
18346 Moschato, Athens, Greece  
T: +30 210 4839700  
E: info@pks-hendi.com

### HENDI Italia S.R.L.

Via Leonardo da Vinci 4  
39100 Bolzano (BZ), Italy  
T: 800 727 438  
E: office.italy@hendi.eu