



CK7310X1

Counter Cooler GN1/1

Product Features

- Stainless steel
- Ventilated cooling
- Controller with Bluetooth and NFC connectivity
- Automatic defrost
- Self-closing doors
- Removable table top without splashback
- Adjustable legs

Stainless steel counter cooler with GN1/1 shelves

The CK7310X1 is an energy-efficient counter cooler for professional settings. It has a 42% lower energy consumption compared to the previous CK7310 /-SPmodel. The CK counter cooler is made for professional kitchens, and it offers an ideal solution for keeping ingredients chilled and within easy reach during service. It is made from durable SS304 stainless steel and features automatic defrost and GN1/1 dimensioned shelves for easy cleaning and smooth workflows. Its ventilated cooling system keeps contents at a consistent temperature, and the electronic controller makes it easy to adjust the temperature to fit your ingredients. The controller has Bluetooth and NFC-connectivity. This means that you via an app can control the lighting, keep an eye of the temperature of the cabinet, and even export data for easy reporting. It has a tabletop which can be removed if you wish to use it as an undercounter cooler and add your own tabletop. The legs are adjustable so it is possible to adapt the height of the table to your needs. The CK counter cooler makes an excellent addition to any professional kitchen.

Measures and Content

Temperature Range	°C	-2 to +8
Climate Class		5
Gross / Net Weight	kg	151 / 134
Gross / Net Volume	l	368 / 291

Design and Material

Door No & Type	3 hinged self-closing doors
Shelves No & Type	3 wire shelves white
Shelf Color	White
Feet / Legs	4 adjustable feet
Exterior Finish	SS304
Interior Finish	SS304
Lock	No

Cooling and Functions

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic
Refrigerant	R600a
Refrigerant Charge	g95
Thermometer	Yes

Power and Consumption

Energy Class		A
Energy Consumption	kWh/24h	1.42
Annual Energy Cons.	kWh/year	518
Input Power	W	300
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

Dimensions

Internal Dimension (WxDxH)	mm	1234 x 580 x 564
External Dimension (WxDxH)	mm	1795 x 700 x 860
Packed Dimension (WxDxH)	mm	1825 x 730 x 910
40ft Container Load	pcs	38



Easy access to clean dust filter



Drawers available as separate kit