



## BA21H

## Backbar Cooler


## **Product Features**

- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- · Ventilated cooling for fast pull-down and even temperature
- Energy saving variable speed compressor
- Double glazed tempered glass
- Hinged alu-framed glass doors
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light
- Lock

## High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat. The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has hinged aluminium doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility. The BA range is also available in a variant with selfclosing sliding doors.

Measures and Content		
Total Display Area	m²	0.52
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	70 / 64
Gross / Net Volume	I	196 / 188
Design and Material		
Door No & Type		2 hinged glass doors
Door Reversible		No
Tempered glass		Yes
Shelves No & Type		4 wire shelves chrome
Shelf Color		Chrome
Shelf Dimensions		395x328 mm
Feet / Legs		4 adjustable feet
Exterior Finish		Black
Interior Finish		Stucco aluminium
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	70
Thermometer		Yes
Power and Consumption		
Energy Class		A
Energy Consumption	kWh/24h	1.08
Annual Energy Cons.	kWh/year	394
Max Ambient		30°C at 55% RH
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44
Dimensions		
Internal Dimension (WxDxH)	mm	810 x 418 x 734
External Dimension (WxDxH)	mm	900 x 520 x 900
Packed Dimension (WxDxH)	mm	985 x 575 x 970
40ft Container Load	pcs	96





Adjustable wire shelves

Electronic thermostat