



LPD1200F/BLACK

Refrigerated Display Counter

Product Features

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Rear glass sliding doors
- Adjustable feet and castors
- Flat top/glass top
- Double glazed glass
- Anti mist front glass

Refrigerated display counter with flat glass front and top

The LPD is our high-quality range of refrigerated display counters. It is made of quality materials and has key features such as an anti-mist front, double glazed glass to reduce energy consumption and running costs, and LED lights under each of the frosted glass shelves. The refrigerated glass counter has an efficient ventilated cooling system that keeps food, pastries, and cakes looking fresh, while sliding doors to the rear allow easy loading and serving. The LPD range is available in several sizes and also in a model with a curved glass front.

Measures and Content

| | | |
|--------------------|----|-----------|
| Total Display Area | m² | 1.85 |
| Temperature Range | °C | +2 to +8 |
| Climate Class | | 3 |
| Gross / Net Weight | kg | 273 / 232 |
| Gross / Net Volume | l | 377 / 191 |

Design and Material

| | |
|-------------------|--------------------------|
| Door No & Type | 2 sliding glass doors |
| Tempered glass | Yes |
| Shelves No & Type | 2 glass shelves + base |
| Shelf Dimensions | 105x33 / 105x33 / 105x44 |
| Feet / Legs | 4 adjustable feet |
| Castors | 4 castors |
| Exterior Finish | Stainless steel / Glass |
| Interior Finish | Stainless steel / Glass |
| Interior Light | LED |

Cooling and Functions

| | |
|--------------------|------------|
| Type of Controller | Electronic |
| Type of Cooling | Ventilated |
| Type of Defrost | Automatic |
| Refrigerant | R290 |
| Refrigerant Charge | g130 |
| Thermometer | Yes |

Power and Consumption

| | | |
|---------------------|----------|------------|
| Energy Class | | D |
| Energy Consumption | kWh/24h | 11.13 |
| Annual Energy Cons. | kWh/year | 4062 |
| Input Power | W | 580 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 48 |

Dimensions

| | | |
|----------------------------|-----|-------------------|
| Internal Dimension (WxDxH) | mm | 1140 x 510 x 670 |
| External Dimension (WxDxH) | mm | 1205 x 745 x 1209 |
| Packed Dimension (WxDxH) | mm | 1260 x 800 x 1320 |
| 40ft Container Load | pcs | 46 |



Pastry display



Sliding doors