



## SFI250-CF VS

Supermarket Cooler / Freezer

### Product Features

- Easily switchable between cooler and freezer
- Energy saving variable speed compressor
- Excellent product visibility
- Sliding curved lids
- Ideal in combination with our top section MTF
- Adjustable false base
- LED interior light
- Bumper bars
- Union kit for island creation is available as option

Supermarket cooler / freezer with curved glass for full visibility

The SFI cooler / freezer is perfect for displaying products in supermarkets, grocery stores, butchers, pet food stores etc. The curved glass sliding lids allow full visibility of the products inside. The energy efficient LED interior lighting on the back wall of the freezer, illuminates the products beautifully. The LED light has its own separate power cord, so it can be connected to the rest of the light in the store and be turned off at night to save energy. The supermarket cooler / freezer can be arranged into islands with a head case on each end or below a MTF top section. The variable speed compressor ensures that the unit only regulates the temperature when needed. This makes it app. 20% more energy efficient compared to the same model without a variable speed compressor – and thereby more cost efficient to operate. The SFI range also comes as a freezer option as well as in several colors - contact our sales team for more information.

Measures and Content		
Total Display Area	m <sup>2</sup>	1.73
Temperature Range	°C	-24 to -18 / -1 to +8
Climate Class		4
Gross / Net Weight	kg	220 / 201
Gross / Net Volume	l	1104 / 718
Design and Material		
Lid No & Type	2 curved sliding glass lids	
Basket No & Type		
Divider System	Yes	
Number of dividers	pcs	5
Feet / Legs	6 adjustable legs	
Exterior Finish	White	
Interior Finish	White painted steel	
Interior Light	LED Horizontal	
Cooling and Functions		
Type of Controller	Electronic	
Type of Cooling	Static	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	130
Thermometer	Yes	
Power and Consumption		
Energy Class	C	
Energy Consumption	kWh/24h	5.51
Annual Energy Cons.	kWh/year	2011.15
Power	1	
Max Ambient	30°C at 55% RH	
Input Power	W	890
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48
Dimensions		
Internal Dimension (WxDxH)	mm	2370 x 720 x 627
External Dimension (WxDxH)	mm	2506 x 858 x 890
Packed Dimension (WxDxH)	mm	2570 x 915 x 980
40ft Container Load	pcs	16



Digital controller



Adjustable false base