



SFI250B-CF VS

Black Supermarket Cooler / Freezer

Product Features

- Easily switchable between cooler and freezer
- Energy saving variable speed compressor
- Excellent product visibility
- Sliding curved lids
- · Ideal in combination with our top section MTF
- Adjustable false base
- LED interior light
- Bumper bars
- Union kit for island creation is available as option

Black supermarket cooler / freezer with curved glass for

The SFI cooler / freezer is perfect for displaying products in supermarkets, grocery stores, butchers, pet food stores etc. The curved glass sliding lids allow full visibility of the products inside. The energy efficient LED interior lighting on the back wall of the freezer, illuminates the products beautifully. The LED light has its own separate power cord, so it can be connected to the rest of the light in the store and be turned off at night to save energy. The supermarket cooler / freezer can be arranged into islands with a head case on each end or below a MTF top section. The variable speed compressor ensures that the unit only regulates the temperature when needed. This makes it app. 20% more energy efficient compared to the same model without a variable speed compressor – and thereby more cost efficient to operate. The SFI range also comes as a freezer option as well as in several colors - contact our sales team for more information.

Measures and Content		
Total Display Area	m²	1.73
Temperature Range	°C	-24 to -18 / -1 to +8
Climate Class		4
Gross / Net Weight	kg	220 / 201
Gross / Net Volume	I	1104 / 718
Design and Material		
Lid No & Type		2 curved sliding glass lids
Basket No & Type		
Divider System		Yes
Number of dividers	pcs	5
Feet / Legs		6 adjustable legs
Exterior Finish		Black
Interior Finish		White painted steel
Interior Light		LED Horizontal
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	130
Thermometer		Yes
Power and Consumption		
Energy Class		C
Energy Consumption	kWh/24h	5.51
Annual Energy Cons.	kWh/year	2011.15
Power		1
Max Ambient		30°C 55% RH
Input Power	W	890
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48
Dimensions		
Internal Dimension (WxDxH)	mm	2370 x 720 x 627
External Dimension (WxDxH)	mm	2506 x 858 x 890
Packed Dimension (WxDxH)	mm	2570 x 915 x 980
40ft Container Load	pcs	16





Digital controller

Adjustable false base