



PDC126 VS SL LED

Black impulse cooler

Product Features

- Energy saving variable speed compressor
- Plexi glass sides for great product visibility
- Impressive storage space
- Tilting function for better product display
- LED interior light
- 4 solid castors, 2 with brakes
- Bumper bars on 4 sides
- Maintenance free condenser

Energy efficient impulse cooler with glass lids

The PDC impulse cooler is all about showcasing the products inside. It has clear plexi glass on all four sides as well as easy sliding glass lids on the top. Furthermore, it comes with two horizontal LED light strips. This provides a fantastic product visibility no matter from which direction the customer sees it. If the cooler is placed against a wall, it can be tilted 15 degrees for a better product display. The island cooler has a variable speed compressor as well as highly efficient EC fans, allowing for a more silent and energy efficient operation. This is a unique feature for this kind of product. The unit is easy to move with tubular 360 degree bumper bars as well as strong casters with brakes. That way you can always relocate it to wherever the need is biggest in your store. In terms of maintenance, the impulse cooler has a maintenance free condenser as well as a stainless steel bottom plate to ensure easy cleaning.

Measures and Content

Total Display Area	m ²	1.51
Temperature Range	°C	-1 to +5
Climate Class		3
Gross / Net Weight	kg	176 / 133
Gross / Net Volume	l	408 / 190

Design and Material

Lid No & Type		2 curved sliding glass lid
Castors		4 wheels, 2 with brake
Exterior Finish		Black / Glass
Interior Finish		Stainless steel / Glass
Interior Light		2 x Vertically LED
Lock		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic-Off Cycle
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes

Power and Consumption

Energy Class		D
Energy Consumption	kWh/24h	5.25
Annual Energy Cons.	kWh/year	1916
Max Ambient		25°C at 60% RH
Input Power	W	700
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	52

Dimensions

Internal Dimension (WxDxH)	mm	1210 x 1080 x 342
External Dimension (WxDxH)	mm	1405 x 1210 x 1005
Packed Dimension (WxDxH)	mm	1335 x 1170 x 1140
40ft Container Load	pcs	36



Sliding glass lids



LED light