

SPECIFICATIONS

AO Medium	TeO ₂		
Acoustic Velocity	4.2 mm/μs		
Active Aperture*	2.5 mm 'L' X	1.5 mm 'H'	
Center Frequency (Fc)	200 MHz		
RF Bandwidth	50 MHz @	-10 dB Return Loss	
Input Impedance	50 Ohms Nominal		
VSWR @ Fc	1.3 :1 Max		
Wavelength	470-690 nm		
Insertion Loss	4 % Max		
Reflectivity per Surface	1 % Max		
Anti-Reflection Coating	MIL-C-48497		
Optical Power Density	250 W/mm ²		
Contrast Ratio	1000 :1 Min		
Polarization	90 ° To Mounting Plane		

PERFORMANCE VS WAVELENGTH


Wavelength (nm)	470	532	633	690
Saturation RF Power (W)	0.4	0.6	0.9	1.1
Bragg Angle (mr)	11.2	12.7	15.1	16.4
Beam Separation (mr)	22.4	25.4	30.2	32.8

PERFORMANCE VS BEAM DIAMETER

Beam Diameter (μm)	1000	1000	1000	1000
at Wavelength (nm)	470	532	633	690
Diffraction Efficiency (%)	85	85	85	85
Rise Time (nsec)	159	159	159	159

*Active Aperture: Aperture over which performance specifications apply.

Outline Drawing:



Document

10/31/13

Control

Notes:

- 1) All dimensions in inches unless specified otherwise.
- 2) cover Nickel plated

THIS DOCUMENT IS THE PROPERTY OF GOOCH AND HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF GOOCH AND HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH AND HOUSEGO.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	T. NG 10/8/2013	 AOMO 3200-1214 200 MHz Frequency Shifter		
MATERIAL:	CHK				
FINISH:	APP				
	APP				
			PART NUMBER:	97-03036-02	REV: 2
			SHEET 1 OF 1		