

SPECIFICATIONS

AO Medium	TeO ₂
Acoustic Velocity	.68 mm/μs
Active Aperture*	2.5 mm Dia
RF Frequency Range	55-100 MHz
RF Bandpass (FWHM)	915 KHz @ 488 nm
Wavelength Range	400-650 nm
VSWR	2.8 :1 Max
Input Impedance	50 Ohms Nominal
Insertion Loss	5 % Max
Temperature Sensitivity	0.05 nm/C
Diffacted Beam Collinearity, min deviation	0.01 degrees
Input Optical Polarization	Vertical
Output Optical Polarization	Horizontal
Max RF Power	2 watt

Document

04/05/17

Control


Special Testing

Diffraction Efficiency
(per wavelength input divergence < 2 mrad)

Min	Units	Max
90	%	

Outline Drawing:

Package 97-03151-03-15rA



Notes:

Simultaneous Diffraction, any 8 wavelengths
Max RF Power with 8 Simultaneous Frequencies = 2W
VSWR 2.8:1 = 6.5 dB Return Loss.

THIS DOCUMENT IS THE PROPERTY OF GOOCH AND HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES GOOCH AND HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH AND HOUSEGO.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	G. Scholz 4/3/2017	Gooch & Housego		
MATERIAL:	CHK		DESCRIPTION: AOTF PCAOM VIS 400-650		
FINISH:	APP				
	APP		PART NUMBER: 97-03151-04	REV: A	SHEET 1 OF 1

*Active Aperture: Aperture over which performance specifications apply.