

SPECIFICATIONS

RF Input (each channel)

Input Impedance	50 Ohms
Power Input	-5 dBm nominal, +5 dBm Max
Connector	SMB Male

RF Output (each channel)

Output Power @ 220 MHz	2.5 W
Rise/Fall Time	11 nsec typical
RF Bandwidth	+/-30MHz
2nd Harmonic Distortion @ 220 MHz	-20 dBc Max
3rd Harmonic Distortion @ 220 MHz	-15 dBc Max
Output Impedance	50 Ohms
Output VSWR @ 220 MHz	1.5 : 1 Max
Output VSWR over Bandwidth	2.0 : 1 Max
RF Level Adjustment Range	15 dB
Output Connector	SMA Female


System Specifications

Power Supply Voltage	+28 V @ 4.2 A
Operating Temperature Range	0 < Ta < 70° C
Number of Channels	5

1. Output power factory set to 2.5 W with -5 dBm single tone input at 220 MHz. Power stability less than 5% over the heat sink's ambient temperature range of 0 - 70° C, after 5 minute warm-up.

2. Each separate channel module includes a 2-pin connector pigtail for the power connection. Power is supplied by mating with a 2-pin connector attached to one of the unit's two terminal blocks.

OUTLINE DRAWING



Document

07/09/19

Control

THIS DOCUMENT IS THE PROPERTY OF GOOCH AND HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF GOOCH AND HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH AND HOUSEGO.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	TOM NG 6/25/2019	Gooch & Housego		
MATERIAL: RoHS	CHK		DESCRIPTION: AODR MC220 RFHIC		
FINISH: Compliant	APP		AMP MODULE, 5CH, 220MHz		
	APP		PART NUMBER: 97-02903-05	REV: A	1 of 1

Confidential, For Internal Use Only