

SPECIFICATIONS

RF Input (each channel)

Input Impedance 50 Ohms
Power Input -5 dBm nominal, +5 dBm Max
Connector SMB Male

RF Output (each channel)


Output Power @ 300 MHz 2.5 W
Rise/Fall Time 5 nsec typical
RF Bandwidth +/-30MHz
2nd Harmonic Distortion @ 300 MHz -20 dBc Max
3rd Harmonic Distortion @ 300 MHz -15 dBc Max
Output Impedance 50 Ohms
Output VSWR @ 300 MHz 1.5 : 1 Max
Output VSWR over Bandwidth 2.0 : 1 Max
RF Level Adjustment Range 15 dB
Output Connector SMA Female

System Specifications

Power Supply Voltage +28 V @ 3 A
Operating Temperature Range 0 < Ta < 70° C
Number of Channels 3

1. Output power factory set to 2.5 W with -5 dBm single tone input at 300 MHz. Power stability less than 5% over the heat sink's ambient temperature range of 0 - 70° C, after 5 minute warm-up.

OUTLINE DRAWING



Document

07/12/18

Control

THIS DOCUMENT IS THE PROPERTY OF GOOCH AND HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF GOOCH AND HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH AND HOUSEGO.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	Geri Scholz 7/10/2018			
MATERIAL:	CHK		AODR MC300 AMP MODULE 3CH, 300MHz		
FINISH:	APP				
	APP		PART NUMBER:	97-03352-02	REV: 1
			1 of 1		

Confidential, For Internal Use Only