

# Lamps with metal bases P21W

Original spare part



### The cost-effective original spare parts

ORIGINAL signal lamps with metal bases feature - like all ORIGINAL products from OSRAM - a reliable OEM quality. Due to the wide product range, the lamps can be used as original spare lamps for different applications.

# Product datasheet

## Technical data

### Product information

Application (Category and Product specific)	Auxiliary lamp
---	----------------

### General Product Information

Global order reference	7506
------------------------	------


### Electrical Data

Power input	25 W
Nominal voltage	12.0 V
Nominal wattage	21 W
Test voltage	13.5 V
Power input tolerance	±6 %

### Photometric Data

Nominal luminous flux	460 lm
Luminous flux tolerance	±15 %

### Physical Attributes & Dimensions



Diameter	26.5 mm
Product weight	7.70 g
Length	52.5 mm
Lamp base	BA15s

### Lifetime Data

Lifespan B3	250 hr
Lifespan Tc	500 hr

## Product datasheet

### Capabilities

Technology	AUX
------------	-----

### Certificates & standards

ECE category	P21W
Approval marks – approval	E1 approval

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172285353   4008321671899   4050300838120   4052899593473   4052899402034   4062172415798   4062172048668   4062172285339   4062172396325   4052899402058   4062172396301   4062172016803   4062172188241   4052899040892   4050300925448   4062172188289   4008321618313   4008321618467   4052899581562   4008321417428   4050300609171
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	No declarable substances contained

### Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300838120	OSRA7506	8328096	-	-
4050300925448	OSRA7506BLI2	-	4730328	-

### Logistical Data



Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300838120	ORIGINAL - METAL BASE P21W	Unpacked 1	25 mm x 25 mm x 52 mm	0.03 dm <sup>3</sup>	8.00 g
4008321090966	ORIGINAL - METAL BASE P21W	Shipping carton box 50	273 mm x 145 mm x 65 mm	2.57 dm <sup>3</sup>	545.00 g
4050300925448	ORIGINAL - METAL BASE P21W	Blister 2	95 mm x 70 mm x 28 mm	0.03 dm <sup>3</sup>	21.00 g
4008321140494	ORIGINAL - METAL BASE P21W	Shipping carton box 20	280 mm x 80 mm x 103 mm	2.31 dm <sup>3</sup>	283.00 g
4062172396301	ORIGINAL - METAL BASE P21W	BLI ECO 2	70 mm x 27 mm x 95 mm	0.03 dm <sup>3</sup>	28.00 g
4062172396318	ORIGINAL - METAL BASE P21W	Shipping carton box 20	164 mm x 124 mm x 78 mm	1.59 dm <sup>3</sup>	316.00 g

## Product datasheet

4062172396325	ORIGINAL - METAL BASE P21W	BLI ECO 2	70 mm x 27 mm x 95 mm	0.03 dm <sup>3</sup>	28.00 g
4062172396332	ORIGINAL - METAL BASE P21W	Shipping carton box 20	164 mm x 124 mm x 78 mm	1.59 dm <sup>3</sup>	316.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File	
	User instruction GPRS_Safety symbols instructions
	ref_pim_amsproduct360degreeimages ORIGINAL P21W 7506

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM