

ULTRA LIFE PY21W

Up to four times longer lifetime




Extra lifetime

Up to four times longer lifetime compared to standard auxiliary lamps



More durability

For longer replacement cycles and additional reliability and comfort



Wide product range

Fits for most common auxiliary lamp types



The durable light with up to four times longer lifetime

With ULTRA LIFE, you choose durable signal lamps for your car. The lamps provide a long life span - up to four times longer lifetime compared to standard lamps - and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). They are therefore ideal for frequent drivers.

Technical data

Product information

Application (Category and Product specific)	Auxiliary lamp
---	----------------

General Product Information

Global order reference	7507ULT
Product remark	Amber lamp for clear indicators


Electrical Data

Power input	25 W
Nominal voltage	12.0 V
Nominal wattage	21 W
Power input tolerance	±6 %
Test voltage	13.5 V

Photometric Data

Nominal luminous flux	280 lm
Luminous flux tolerance	±20 %

Physical Attributes & Dimensions



Lamp base	BAU15s
Length	52.5 mm
Diameter	25.0 mm
Product weight	8.06 g

Lifetime Data

Lifespan B3	500 hr
Lifespan Tc	1000 hr

Product datasheet

Capabilities

Technology	AUX
------------	-----

Certificates & standards

ECE category	PY21W
--------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321415165 4062172394871 4008321413147
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321413147	OSRA7507ULT	-	-	-

Logistical Data



Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321413147	ULTRA LIFE PY21W	Unpacked 1	52 mm x 25 mm x 25 mm	0.35 dm ³	8.00 g
4008321413161	ULTRA LIFE PY21W	Shipping carton box 50	273 mm x 145 mm x 65 mm	2.57 dm ³	563.00 g
4008321415165	ULTRA LIFE PY21W	Blister 2	135 mm x 95 mm x 26 mm	0.35 dm ³	27.00 g
4008321415172	ULTRA LIFE PY21W	Shipping carton box 20	279 mm x 115 mm x 146 mm	4.68 dm ³	350.00 g
4062172394871	ULTRA LIFE PY21W	BLI ECO 2	95 mm x 27 mm x 135 mm	0.35 dm ³	26.00 g
4062172394888	ULTRA LIFE PY21W	Shipping carton box 20	156 mm x 144 mm x 110 mm	2.47 dm ³	311.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File

Product datasheet

	User instruction GPRS_Safety symbols instructions
	ref_pim_amsproduct360degreeimages ULTRA LIFE PY21W 7507ULT

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM