

PRODUCT INFORMATION



Lubricants – Transmission Oils – Automotive

Version: 277/03

Valvoline™ Light & Heavy Duty Axle Oil 80W-90

Axle oil for passenger cars, trucks and buses.

EP axle oil suitable for differentials and transaxles where the manufacturer specifies GL-5 oil.

Performance levels

API: GL-5

ZF TE-ML 07A, 08

Applications

Valvoline Light & Heavy Duty Axle Oil 80W-90 provides increased protection and lubrication of the differential and the transaxle over a wide temperature range.

Suitable for differentials and transaxles of passenger cars, trucks and buses where the manufacturer recommends GL-5 transmission oil with a viscosity of SAE 80W-90.

Not for limited slip applications.

Features & Benefits

Increased protection

Increased protection against wear and tear, also under high stress working conditions.

Advanced additives

Modern additives protect against corrosion, oxidation, foaming and deposits.

Breakdown resistance

Quality base oils and a highly balanced additive system avoid breakdowns even after long-time use.

Consistent, stable viscosity

Increased viscosity-temperature properties even at very low temperatures. Highly stable viscosity with long-term multigrade advantages.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com or <https://pisheets.valvoline.com/>

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline Light & Heavy Duty Axle Oil	
SAE Viscosity Grade	80W-90
Viscosity, mm²/s @ 100 °C. ASTM D-445	14,7
Viscosity, mm²/s @ 40 °C. ASTM D-445	132,8
Viscosity Index ASTM D-2270	111
Viscosity, mPa.s -26°C. ASTM D-5293	<150.000
Pour Point, °C ASTM D-5950	-39
Specific Gravity @ 15.6°C. ASTM D-4052	0,880
Flash Point, COC, °C. ASTM D-92	216

**This information only applies to products manufactured in the following location(s):
Europe**

™ Trademark of Valvoline, registered in various countries © 2021

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 277/02